NSN 5305-00-536-6828

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-536-6828 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.352 inches and 0.403 inches **Fastener Length:** Between 1.914 inches and 1.934 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.189 inches and 0.204 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3737 inches and 0.3742 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.375 inches and 1.391 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.786 inches first hole and 1.806 inches first hole Surface Finish: 32.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

NSN 5305-00-536-6828

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0