

View Online at <https://aerobasegroup.com/nsn/5305-00-536-6830>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.352 inches and 0.403 inches

Fastener Length:

Between 4.851 inches and 4.871 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.189 inches and 0.204 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3737 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Grip Length:

Between 4.312 inches and 4.328 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.723 inches first hole and 4.743 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Retaining element in shank

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0