NSN 5305-00-536-6831

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-536-6831
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.351 inches and 0.402 inches
Fastener Length:
Between 5.226 inches and 5.246 inches
Head Style:
Crowned hexagon
Head Height:
Between 0.189 inches and 0.204 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3737 inches and 0.3742 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.375 inches
Grip Length:
Between 4.688 inches and 4.704 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
5.099 inches first hole and 5.119 inches first hole
Surface Finish:
32.0 microinches grip
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

Unjf

NSN 5305-00-536-6831

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0