

View Online at <https://aerobasegroup.com/nsn/5305-00-536-7057>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

3.125 inches

Fastener Length:

Between 4.360 inches and 4.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.852 inches and 1.875 inches

Head Height:

Between 1.236 inches and 1.250 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

1.250 inches

Width Across Flats:

Between 0.875 inches and 0.885 inches

Thread Qty Per Inch (tpi):

7

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Special Features:

Finish color black

Material:

Steel fastener

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924, class 3 military specification single treatment response fastener

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.