

View Online at <https://aerobasegroup.com/nsn/5305-00-536-7057>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

3.125 inches

**Fastener Length:**

Between 4.360 inches and 4.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.852 inches and 1.875 inches

**Head Height:**

Between 1.236 inches and 1.250 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

1.250 inches

**Width Across Flats:**

Between 0.875 inches and 0.885 inches

**Thread Qty Per Inch (tpi):**

7

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Special Features:**

Finish color black

**Material:**

Steel fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924, class 3 military specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.