

NSN 5305-00-536-8556 Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-536-8556 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.500 inches and 0.540 inches **Fastener Length:** Between 0.609 inches and 0.649 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.091 inches and 0.106 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 20.0 rockwell c and 36.0 rockwell c **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style: Primary Washer Outside Diameter:** 

0.250 inches

**Secondary Washer Outside Diameter:** 

0.312 inches

**Primary Washer Style:** 

Split helical ring

**Primary Washer Material Thickness:** 

0.032 inches

**Secondary Washer Material Thickness:** 

0.032 inches

Material:

Steel comp 1010 or steel comp 1020

**Surface Treatment:** 

Cadmium

## NSN 5305-00-536-8556

Assembled Washer Screw - Page 2 of 2



|  | Surface | <b>Treatment</b> | Specification: |
|--|---------|------------------|----------------|
|--|---------|------------------|----------------|

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0