Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-536-9929

Thread Cl	ass:
2a	
Thread Di	rection:
Right-hand	I
Thread Le	ngth:
Between 0	.123 inches and 0.169 inches
Fastener I	_ength:
Between 0	.407 inches and 0.438 inches
Head Style	9:
Pan	
Head Dian	neter:
Between 0	.205 inches and 0.219 inches
Head Heig	Jht:
Between 0	.070 inches and 0.080 inches
First Diam	eter From Head:
0.078 inch	es
Distance I	From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0	.269 inches and 0.284 inches
Internal D	rive Style:
Cross rece	ess type 1
End Appli	cation:
An/alr-56c	
Thread Dia	ameter:
0.112 inch	es
Thready C	tty Per Inch (tpi):
40	
Min. Tens	ile Strength (psi):
80000 pou	nds per square inch
Externally	Relieved Body Diameter Quantity:
1	
Material:	
Stainless s	teel
Material S	pecification:
Qq-s-763,	300 series federal specification single material response or 66, 300 series federal standard single material response or comp
16-18 or 1	8-8 assn standard single material response
Surface T	reatment:
Passivate	
Surface T	reatment Specification:
Mil-f-14072	2, finish e300 military specification single treatment response
Thread Se	ries Designator:
Unc	
Shelf Life:	
N/a	

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.