## NSN 5305-00-537-0144

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-537-0144 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.521 inches and 0.541 inches **Fastener Length:** Between 1.077 inches and 1.124 inches **Head Style:** Flat countersunk **Head Diameter:** 0.757 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8735 **Screw Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-6098 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A500d0

## NSN 5305-00-537-0144

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.