NSN 5305-00-541-6343

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-541-6343 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.719 inches **Fastener Length:** 1.375 inches **Head Style:** Hexagon **Head Height:** 0.406 inches Width Between Flats: 0.875 inches **Hole Diameter:** 0.125 inches First Diameter From Head: 0.500 inches **Second Diameter From Head:** 0.688 inches **Third Diameter From Head:** 0.437 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.531 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.656 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.500 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 30.0 rockwell c and 35.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

NSN 5305-00-541-6343

A003b0

Externally Relieved Body Screw - Page 2 of 2



Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 4140 or steel comp 8640 or steel comp 8740
Surface Treatment:
Cadmium or cadmium and chromate or cadmium and phosphate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: