NSN 5305-00-541-9319

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-541-9319 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.735 inches and 0.802 inches **Fastener Length:** Between 1.995 inches and 2.042 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.950 inches and 1.017 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas672 assn standard single treatment response or mil-c-8873 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-541-9319

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8873 spec.