## NSN 5305-00-543-2335

Between 0.236 inches and 0.355 inches

2a

**Thread Direction:** 

Fastener Length:

0.375 inches **Head Style**:

Right-hand

Thread Length:



Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-543-2335

Thread Class:

-an
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Washer Quantity:
1
nternal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
40.0 rockwell c primary washer and 50.0 rockwell c primary washer
Primary Washer Outside Diameter:
Between 0.365 inches and 0.381 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.020 inches and 0.025 inches
Material:
Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washe
or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary
washer or steel comp 1561 primary washer or steel comp 1566 primary washer
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Designator:
Jnc
Shelf Life:
N/a
Unit Of Measure:
-

## NSN 5305-00-543-2335

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0