NSN 5305-00-543-4383

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-543-4383 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.803 inches and 0.865 inches **Fastener Length:** Between 0.865 inches and 0.895 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate or zinc and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-p-416, type 2, cl 2 federal specification 2nd treatment response or qq-z-325, type 2, cl 2 federal specification 3rd treatment response or qq-z-35, type 2, cl 2 federal specification 4th treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-543-4383

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0