## NSN 5305-00-543-5063

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-543-5063

| view Offiline at https://aerobasegroup.com/hisri/5505-50-545-5005  |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.200 inches and 0.250 inches  |
| Fastener Length:   |
| Between 0.219 inches and 0.250 inches  |
| Head Style:  |
| Fillister  |
| Head Diameter:   |
| Between 0.166 inches and 0.183 inches  |
| Head Height:   |
| Between 0.072 inches and 0.079 inches  |
| Hole Diameter:   |
| 0.037 inches   |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.112 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):  |
| 40   |
| Min. Tensile Strength (psi):   |
| 60000 pounds per square inch   |
| Screw Material:  |
| Steel  |
| Screw Material Specification:  |
| Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal     |
| specification single material response or qq-w-405 federal specification single material response  |
| Screw Surface Treatment:   |
| Cadmium or zinc  |
| Screw Surface Treatment Specification:   |
| Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response |
| Head Hole Configuration Style:   |
| Round  |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5305-00-543-5063

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0