

NSN 5305-00-543-5800 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-543-5800 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.460 inches and 1.810 inches **Fastener Length:** Between 2.460 inches and 2.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Hole Diameter:** 0.064 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi): 170000 pounds per square inch

Minimum Yield Strength: 150000 pounds per square inch Hole Configuration Style: Round internal hexagon

Material Specification:

Surface Treatment:

Cadmium and chromate

38.0 rockwell c and 45.0 rockwell c

66 federal standard single material response

Hardness Rating:

Material: Steel

NSN 5305-00-543-5800

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0