NSN 5305-00-543-5917

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-543-5917 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.438 inches **First Diameter From Head:** 0.130 inches **Second Diameter From Head:** 0.190 inches **Third Diameter From Head:** 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.594 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.750 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 57.0 rockwell b and 77.0 rockwell b **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:**

Surface Treatment:

Astm a582 federal specification single material response

Nickel

NSN 5305-00-543-5917

Externally Relieved Body Screw - Page 2 of 2



Surface ⁻	Treatment S	Specification:
----------------------	-------------	----------------

Qq-n-290, ty v, matte federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0