NSN 5305-00-546-4835

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-546-4835

•
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.699 inches and 0.729 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.3390 inches and 0.3813 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
3180 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches
Material:
Steel comp 4130
Material Specification:
Mil-s-6758 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1503 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-00-546-4835

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.