## NSN 5305-00-546-6866

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-546-6866           |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.130 inches  |
| Fastener Length:  |
| 0.427 inches  |
| Head Style:   |
| Fillister   |
| Head Diameter:  |
| Between 0.166 inches and 0.183 inches                                   |
| Head Height:  |
| Between 0.049 inches and 0.083 inches                                   |
| First Diameter From Head:   |
| Between 0.084 inches and 0.088 inches                                   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.225 inches and 0.245 inches                                   |
| Internal Drive Style:   |
| Slot  |
| Thread Diameter:  |
| 0.112 inches  |
| Thready Qty Per Inch (tpi):   |
| 40  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Material:   |
| Steel comp 303  |
| Material Specification:   |
| Astm a582 assn standard single material response                        |
| Surface Treatment:  |
| Oxide   |
| Surface Treatment Specification:  |
| Mil-c-13924 cl2 military specification single treatment response        |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5305-00-546-6866

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.