## NSN 5305-00-548-2512

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-548-2512 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.064 inches and 0.125 inches **Fastener Length:** Between 0.095 inches and 0.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.112 inches and 0.118 inches **Head Height:** Between 0.070 inches and 0.073 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-00-548-2512

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0