

View Online at <https://aerobasegroup.com/nsn/5305-00-548-5081>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.317 inches

**Fastener Length:**

Between 0.635 inches and 0.682 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.297 inches and 0.302 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4340 or steel comp 4140 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

76823-51b581 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0