Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-550-2522

Thread Direction: 3a Thread Direction: Nead Di	
Rigen-kand Rigen-kand 1. Add lengh: 0.438 indes Basten-Langh: 0.500 inches Head Skyle: Flat chamfer Batton Commercial Batton Commercial 0.500 inches Head Diameter: 0.500 inches Head Diameter: 0.500 inches Head Height: 0.500 inches Head Diameter From Head: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.502 inches Internal Drive Style: Cross receas type 1 Thread Diameter: 0.375 inches Thread Y Per Inch (pl): 16 Externally Relieved Body Diameter Quantity: 1 Marcial: State compt 1020 State compt 1020 State compt 1020 Cuadmum Interd Series Designator:	Thread Class:
Right-hand Horead Length: 0.438 incles Fastener Length: 0.500 incles Head Style: Flat chamfer Head Diameter: 0.500 incles Head Height: 0.500 incles Flat chamfer From Head: 0.500 incles Distance From Head: 0.502 incles Distance From Head: 0.502 incles Distance From Lengest Bearing Surface Of Head To End Of First Diameter: 0.502 incles Distance From Lengest Bearing Surface Of Head To End Of First Diameter: 0.502 incles Internal Drive Style: Costa recess type 1 Thread Diameter: 0.503 incles Interad Diameter: 0.504 incles Interad Diameter: 0.505 incles Startical Keileved Body Diameter Quantity: 1 Material: Startical Keileved Body Diameter Quantity: 1 Material: Startical Keileved Body Diameter Quantity: Cardinuin Thread Starting Lenge Lenge Lenge Lenge	
Thread Length: 0.438 inches Faster Length: 0.500 inches Head Style: Flat chamter Head Style: Flat chamter 0.600 inches Head Height: 0.500 inches First Diameter From Head: 0.502 inches Distance From Leads 0.602 inches Distance From Leads Distance From Leads Oingtinches Distance From Leads Distance Distance Distance Distance Distance Distance Distance Distance Distance <	
0.438 inches Pastener Length: 0.500 inches Head Skyle: Bit chamfer Bat bamfers: 0.500 inches Head Height: 0.500 inches Fist Diameter From Head: 0.298 inches Distance From Head: 0.298 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.498 inches Bit Barter 108 Marter Surface Toathent:	
Rester Length: 0.500 Inches Head Style: Flact Annifer Head Diameter: 0.500 Inches Head Height: 0.500 Inches First Diameter From Head: 0.502 Inches Distance From Head: 0.602 Inches Circs rescess type 1 Distance From Head (Leip): 0.75 Inches Thread Diameter: 0.75 Inches Ster comp 1020 Ster comp 1020 Ster Comp In20 Ster Comp In20 Chread Evelse Designator: Unc Na Distance Incol Distance Incol Distance Incol	
0.000 inchesHead Style:Flat chamferHead Diameter:0.500 inchesHead Height:0.500 inchesFirst Diameter From Head:0.280 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.602 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesThread Diameter:0.375 inchesThread Val Per Inch (tpl):11Material:Stel comp 1020Surface Totatement:CadmiumThread Series Designator:UncSheft Life:NaUncSheft Life:NaDiameter:NaDiameter: <td>0.438 inches</td>	0.438 inches
Head Style: Flat chamfer Head Diameter: 0.500 inches Head Height: 0.500 inches Head Form Lead: 0.500 inches First Diameter From Head: 0.280 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches Thread Diameter: 0.375 inches Thread Diameter: 0.375 inches Thread Seleved Body Diameter Quantity: 1 Marcia: Starter Treatment: Cadmim Cadmim Thread Series Designator: Na Na Dialization: Na Dialization: Na <td>Fastener Length:</td>	Fastener Length:
Flat chamfer Head Diameter: 0.500 inches Head Height: 0.500 inches First Diameter From Head: 0.298 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.621 inches Internal Drive Style: 0.755 inches Thread Diameter: 0.375 inches Thread Vy Per Inch (tpl): 16 Stater Treatment: Comp Ind0 Starter Treatment: Cadmim Cadmim Starter Treatment: Cadmim Thread Series Designator: Ince Shoft Life: Na Child Measure: Image: Theology Inter Series Image: State Series Designator: Image: Image:	0.500 inches
Head Diameter: 0.500 inches Head Height: 0.500 inches First Diameter From Head: 0.298 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thread Val Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Via Via Firet Infe: Na Singer Series Designator: Singer Series Designator: Na <td< td=""><td>Head Style:</td></td<>	Head Style:
0.500 inchesHead Height:0.500 inchesFirst Diameter From Head:0.289 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.062 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesThread Qty Per Inch (tpi):16Externally Relieved Body Diameter Quantity:1Stel comp 1020Sterlacem 1020Starface Treatment:CadmiumThread Series Designator:UncShafe Itife:NaNaThread Series Designator:NaNaStarface Treatment:NaNaStarface Treatment:NaNaStarface Treatment:NaNaStarface Treatment:NaStarface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:Starface Treatment:	Flat chamfer
Head Height: 0.500 inches First Diameter From Head: 0.288 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thread Valve Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shef Life: Na Material: Na Dird Of Measure: Interd Series Designator: Unc Shef Life: Na Dit Of Measure: Interdeseries	Head Diameter:
0.500 inches First Diameter From Head: 0.298 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Extensily Relieved Body Diameter Quantity: 1 Material: Steel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: Nat Into Measure: - Dird Measure: - Dird Measure: - Dird Measure: - Dird Measure: - Pomiliatrization: No Fig:	0.500 inches
First Diameter From Head: 0.298 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Did Measure: - Ford Measure: - Did Measure: - Dir of Measure: - - Penilitarization: No Fig:	Head Height:
0.238 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: Na Ditt Of Measure: Image: No Fig:	0.500 inches
bistance From Largest Bearing Surface Of Head To End Of First Diameter: 0.062 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: 17 Material: Steel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: Na Shelf Life: Na Dit Of Measure: - Demilitarization: No	First Diameter From Head:
0.062 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesThready Qty Per Inch (tpi):16Externally Relieved Body Diameter Quantity:1Material:Steel comp 1020Surface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUncShelf Life:N/aUnt Of Measure:-Demilitarization:NoFig:	0.298 inches
Interal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesThready Qty Per Inch (tpi):16Externally Relieved Body Diameter Quantity:1Material:Steel comp 1020Surface Treatment:CadmiumThread Series Designator:UncSheff Life:N/aUncSteel comp 102Surface Treatment:UncDiff Life:N/aDiff Life:N/aDiff Life:N/aFig:NoFig:Fig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Cross recess type 1 Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: Externally Relieved Body Diameter Quantity: 1 Material: 1 Material: Steel comp 1020 Surface Treatment: Cadmium Cadmium Cadmium Thread Series Designator: Unc Shelf Life: Na Shelf Life: Na Cinc Demilitarization: No Fig:	0.062 inches
Thread Diameter:0.375 inchesThready Qty Per Inch (tpi):16Externally Relieved Body Diameter Quantity:1Material:Steel comp 1020Surface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnc for Measure:CallDir of Measure:Penilitarization:NoFig:	Internal Drive Style:
0.375 inches Thready Qty Per Inch (tpi): 16 Externally Relieved Body Diameter Quantity: Externally Relieved Body Diameter Quantity: 1 1 Material: 1 Steel comp 1020 Surface Treatment: Cadmium Chread Series Designator: Unc Sheff Life: N/a Sheff Life: N/a Chriet Series S	Cross recess type 1
Thready Qty Per Inch (tpi):16Externally Relieved Body Diameter Quantity:f1Material:Steel comp 1020Surface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aDint of Measure:-Demilitarization:NoFig:	Thread Diameter:
16 Externally Relieved Body Diameter Quantity: 1 1 Material: Steel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Dint of Measure: Demiltarization: No Fig:	0.375 inches
Externally Relieved Body Diameter Quantity:11Material:Steel comp 1020Surface Treatment:CadmiumCadmiumThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):
1 Material: Steel comp 1020 Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Denilitarization: No Fig:	16
Material:Steel comp 1020Surface Treatment:CadmiumCadmiumThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Externally Relieved Body Diameter Quantity:
Steel comp 1020 Surface Treatment: Cadmium Cadmium Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	1
Surface Treatment:CadmiumCadmiseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Steel comp 1020
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	Νο
A003b0	Fiig:
	A003b0