

View Online at <https://aerobasegroup.com/nsn/5305-00-550-3756>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.345 inches and 0.355 inches

Fastener Length:

Between 0.395 inches and 0.405 inches

Head Style:

Fillister

Head Diameter:

Between 0.200 inches and 0.205 inches

Head Height:

Between 0.081 inches and 0.088 inches

First Diameter From Head:

0.040 inches

Second Diameter From Head:

Between 0.121 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.050 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.345 inches and 0.355 inches

Internal Drive Style:

Slot

Thread Diameter:

0.125 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 384

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0