NSN 5305-00-550-3756

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-550-3756 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.355 inches **Fastener Length:** Between 0.395 inches and 0.405 inches **Head Style:** Fillister **Head Diameter:** Between 0.200 inches and 0.205 inches **Head Height:** Between 0.081 inches and 0.088 inches First Diameter From Head: 0.040 inches **Second Diameter From Head:** Between 0.121 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.050 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.345 inches and 0.355 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.125 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303 or steel comp 304 or steel comp 304 or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316I or steel comp 317 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 384 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Fiig:

No