## NSN 5305-00-550-4430

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-550-4430 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.038 inches **Fastener Length:** 0.098 inches **Head Style:** Fillister **Head Diameter:** 0.250 inches **Head Height:** Between 0.020 inches and 0.025 inches **First Diameter From Head:** Between 0.118 inches and 0.120 inches **Second Diameter From Head:** 0.070 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.038 inches and 0.042 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.060 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.099 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-550-4430

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0