## NSN 5305-00-550-9439

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-550-9439 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.418 inches and 0.576 inches **Fastener Length:** Between 1.704 inches and 1.749 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.572 inches and 0.638 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-550-9439

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.