NSN 5305-00-551-7728

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-551-7728

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.541 inches
Fastener Length:
0.625 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.480 inches and 0.531 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
0.156 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Countersink Angle:
Between 80.0 degrees and 82.0 degrees
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

NSN 5305-00-551-7728

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0