Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-557-8564

| Thread Class: | |
|---|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.155 inches and 0.165 inches | |
| Fastener Length: | |
| Between 0.604 inches and 0.614 inches | |
| Head Style: | |
| Knurled no. 1 | |
| Head Diameter: | |
| Between 0.245 inches and 0.255 inches | |
| Head Height: | |
| Between 0.099 inches and 0.119 inches | |
| First Diameter From Head: | |
| Between 0.090 inches and 0.093 inches | |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: | |
| Between 0.439 inches and 0.459 inches | |
| Internal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.138 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Externally Relieved Body Diameter Quantity: | |
| 1 | |
| Material: | |
| Steel comp 303 | |
| Material Specification: | |
| Qq-s-764 federal specification single material response | |
| Surface Treatment: | |
| Passivate | |
| Surface Treatment Specification: | |
| Mil-s-5002 military specification single treatment response | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |

NSN 5305-00-557-8564

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-s-5002 spec.