## NSN 5305-00-558-1083

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-558-1083

view Offiline at https://aerobasegroup.com/hist//3303-00-330-1003
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.750 inches
Fastener Length:
Between 3.281 inches and 3.375 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4340 or steel comp 4140 or steel comp 8740
Screw Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Color:
Black
Thread Series Designator:
Unjf
Specification Data:
80205-nas603 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-558-1083

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.