

View Online at <https://aerobasegroup.com/nsn/5305-00-558-3740>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.158 inches and 0.250 inches

**Fastener Length:**

Between 0.220 inches and 0.250 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Steel comp 4037 or steel comp 8630

**Screw Material Specification:**

-11-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas603 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

spec.