## NSN 5305-00-558-8943

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-558-8943

| View Online at https://aerobasegroup.com/nsn/5305-00-558-8943   |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.438 inches  |
| Fastener Length:  |
| Between 0.470 inches and 0.500 inches   |
| Head Style:   |
| Pan no. 2   |
| Head Diameter:  |
| Between 0.256 inches and 0.270 inches   |
| Head Height:  |
| Between 0.087 inches and 0.097 inches   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.138 inches  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Min. Tensile Strength (psi):  |
| 160000 pounds per square inch   |
| Screw Material:   |
| Steel comp 4037 or steel comp 8630  |
| Screw Material Specification:   |
| Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response |
| Screw Surface Treatment:  |
| Cadmium   |
| Screw Surface Treatment Specification:  |
| Qq-p-416, type 1, cl 3 federal specification single treatment response                                  |
| Thread Series Designator:   |
| Unc   |
| Specification Data:   |
| 80205-nas601 professional/industrial association standard   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A500d0  |
|   |

## NSN 5305-00-558-8943

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

