## NSN 5305-00-559-0134

За

**Thread Direction:** 

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-559-0134

Thread Class:

| Right-hand   |
|--|
| Thread Length:   |
| 0.688 inches   |
| Fastener Length:   |
| 0.688 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.367 inches and 0.375 inches  |
| Head Height:   |
| Between 0.244 inches and 0.250 inches  |
| Hole Diameter:   |
| 0.062 inches   |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.250 inches   |
| Width Across Flats:  |
| Between 0.188 inches and 0.190 inches  |
| Hole Quantity:   |
| 4  |
| Hole Type:   |
| Drilled  |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Min. Tensile Strength (psi):   |
| 123000 pounds per square inch  |
| Hardness Rating:   |
| 26.0 rockwell c and 32.0 rockwell c  |
| Hole Configuration Style:  |
| Round internal hexagon   |
|  |
| Material:  |
| Material:<br>Steel comp 416f   |
|  |
| Steel comp 416f  |
| Steel comp 416f  Material Specification:   |
| Steel comp 416f  Material Specification:  Ams 5610 assn standard single material response                                |
| Steel comp 416f  Material Specification:  Ams 5610 assn standard single material response  Surface Treatment:            |
| Steel comp 416f  Material Specification:  Ams 5610 assn standard single material response  Surface Treatment:  Passivate |

## NSN 5305-00-559-0134

Socket Head Cap Screw - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | 0 | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0