NSN 5305-00-559-4899

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-559-4899 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.574 inches and 0.640 inches **Fastener Length:** Between 2.334 inches and 2.380 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.880 inches and 0.890 inches **Shoulder Diameter:** 0.467 inches first shoulder and 0.468 inches first shoulder **Shoulder Length:** 1.565 inches first shoulder and 1.585 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Product Name:** Navy special project Material: Steel **Material Specification:** 23-105, fscm 76301 mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5305-00-559-4899

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0