NSN 5305-00-559-8145

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-559-8145

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.250 inches and 0.312 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 55000 pounds per square inch
32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material:
32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Head Hole Configuration Style:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Head Hole Configuration Style: Round longitudinal hole
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Head Hole Configuration Style: Round longitudinal hole Thread Series Designator:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Material Specification: Qq-s-633 federal specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification single treatment response Head Hole Configuration Style: Round longitudinal hole Thread Series Designator: Unc

--

NSN 5305-00-559-8145

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0