## NSN 5305-00-559-9064

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-559-9064

| Thread Class:<br>3a<br>Thread Direction:<br>Right-hand<br>Thread Length:<br>Between 0.615 inches and 0.682 inches<br>Fastener Length:<br>Between 0.615 inches and 0.682 inches<br>Fastener Length:<br>Between 1.187 inches and 1.234 inches<br>Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.752 inches and 0.762 inches<br>Grip Diameter:<br>Between 0.752 inches and 0.3742 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.375 inches<br>Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thread Yup Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Surface Treatment:<br>Cadmium   |
|--|
| Thread Direction:Right-handThread Length:Between 0.615 inches and 0.682 inchesFastner Length:Between 1.87 inches and 1.234 inchesHead Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesGrip Length:Between 0.552 inches and 0.572 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Cty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMateriai:SteelSteelSterlation:  |
| Right-handThread Length:Between 0.615 inches and 0.682 inchesFastener Length:Between 1.187 inches and 1.234 inchesHead Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelSterlation:  |
| Thread Length:         Between 0.615 inches and 0.682 inches         Fastener Length:         Between 1.187 inches and 1.234 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.752 inches and 0.762 inches         Grip Diameter:         Between 0.3733 inches and 0.3742 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.375 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Grip Length:         0.375 inches         Min. Tensile Strength (psi):         160000 pounds per square inch         Hardness Rating:         36.0 rockwell c and 40.0 rockwell c         Countersink Angle:         100.0 degrees         Material:         Steel         Steel         Steel         Steel         Sterees:         Sterees:         Sterees:         Sterees:         Sterees:  |
| Between 0.615 inches and 0.682 inchesFastener Length:Between 1.187 inches and 1.234 inchesHead Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelSteelSterlenst:SteelSterlenst:   |
| Fastener Length:Between 1.187 inches and 1.234 inchesHead Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelStere SteelSteelStere SteelSteelStere SteelStere SteelStere SteelStere SteelStere Stere SteelStere Stere Ste |
| Between 1.187 inches and 1.234 inchesHead Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSterlSurface Treatment:   |
| Head Style:Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:30.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSterlStrength:SteelSterlStrength:SteelSterl   |
| Flat countersunkHead Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelSturface Treatment:  |
| Head Diameter:Between 0.752 inches and 0.762 inchesGrip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSterlSurface Treatment:   |
| Between 0.752 inches and 0.762 inches<br>Grip Diameter:<br>Between 0.3733 inches and 0.3742 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.375 inches<br>Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel   |
| Grip Diameter:Between 0.3733 inches and 0.3742 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelSturface Treatment:   |
| Between 0.3733 inches and 0.3742 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.375 inches Grip Length: Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Material: Steel Steel Steel   |
| Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.375 inches<br>Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel   |
| Cross recess type 1<br>Thread Diameter:<br>0.375 inches<br>Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel  |
| Thread Diameter:0.375 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSteelSterlSterlSterl  |
| 0.375 inches<br>Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel   |
| Grip Length:<br>Between 0.552 inches and 0.572 inches<br>Thready Qty Per Inch (tpi):<br>24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel   |
| Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Material: Steel Surface Treatment:   |
| Thready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cCountersink Angle:100.0 degreesMaterial:SteelSurface Treatment:   |
| 24<br>Min. Tensile Strength (psi):<br>160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>36.0 rockwell c and 40.0 rockwell c<br>Gountersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Steel  |
| Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Material: Steel Surface Treatment:  |
| 160000 pounds per square inch<br>Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Surface Treatment:  |
| Hardness Rating:<br>36.0 rockwell c and 40.0 rockwell c<br>Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Surface Treatment:   |
| 36.0 rockwell c and 40.0 rockwell c Countersink Angle: 100.0 degrees Material: Steel Surface Treatment:  |
| Countersink Angle:<br>100.0 degrees<br>Material:<br>Steel<br>Surface Treatment:  |
| 100.0 degrees Material: Steel Surface Treatment:   |
| Material:<br>Steel<br>Surface Treatment:   |
| Steel Surface Treatment:   |
| Surface Treatment:   |
|  |
| Cadmium  |
|  |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |