NSN 5305-00-560-1794

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-560-1794 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.095 inches **Fastener Length:** 0.141 inches **Head Style:** Flat chamfer **Head Diameter:** 0.124 inches **Head Height:** 0.265 inches **First Diameter From Head:** 0.062 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.031 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Test Data Document:** 98230-ono09102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-560-1794

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0