NSN 5305-00-562-7219

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-562-7219 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.080 inches **Fastener Length:** 0.268 inches **Head Style:** Flat chamfer **Head Diameter:** 0.125 inches **Head Height:** 0.075 inches **First Diameter From Head:** Between 0.083 inches and 0.087 inches **Second Diameter From Head:** 0.055 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.095 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.188 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-562-7219

Externally Relieved Body Screw - Page 2 of 2



Ur	۱it	Of	Measure:
----	-----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.