

View Online at <https://aerobasegroup.com/nsn/5305-00-565-5399>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.152 inches

Fastener Length:

Between 0.157 inches and 0.188 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.126 inches and 0.176 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8735 or steel comp 8740 or steel comp 6150

Locking Feature Material:

Plastic polyamide

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response or mil-s-8503 military specification 5th material response

Locking Feature Material Specification:

Mil-f-18240 military specification single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.