## NSN 5305-00-567-5366

Machine Screw - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5305-00-567-5366

Right-hand		
Thread Length:		
Between 0.242 inches and 0.322 inches		
Fastener Length:		
Between 0.302 inches and 0.322 inches		
Head Style:		
Double hexagon w/ hole		
Head Height:		
0.250 inches		
Width Between Flats:		
Between 0.212 inches and 0.220 inches		
Extended Washer Diameter:		
0.312 inches		
Extended Washer Thickness:		
Between 0.030 inches and 0.040 inches		
Hole Diameter:		
0.047 inches		
Internal Drive Style:		
W/o internal drive		
Thread Diameter:		
0.164 inches		
Hole Quantity:		
4		
Thready Qty Per Inch (tpi):		
32		
Min. Tensile Strength (psi):		
130000 pounds per square inch		
Hardness Rating:		
Between 24.0 rockwell c and 35.0 rockwell c		
Screw Material:		
Iron alloy 660		
Screw Material Specification:		
Ams 5735 assn standard single material response		
Head Hole Configuration Style:		
Hexagon flats		
Bearing Surface Of Head Surface Finish:		
63.0 microinches		
Thread Series Designator:		
Unjc		

## NSN 5305-00-567-5366

Machine Screw - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0