NSN 5305-00-570-8736

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-570-8736 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.438 inches and 0.485 inches **Fastener Length:** Between 0.438 inches and 0.485 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.958 inches and 0.987 inches **Head Height:** Between 0.327 inches and 0.348 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-8695 military specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-00-570-8736

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.