

View Online at <https://aerobasegroup.com/nsn/5305-00-571-9576>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.856 inches and 0.938 inches

**Fastener Length:**

Between 0.906 inches and 0.938 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.072 inches and 0.079 inches

**Hole Diameter:**

0.037 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Screw Material:**

Steel comp 8630

**Screw Material Specification:**

Mil-s-6050 military specification single material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response

**Head Hole Configuration Style:**

Round

**Special Features:**

Hole in head located 90 degrees to slot drive

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.