

View Online at <https://aerobasegroup.com/nsn/5305-00-571-9596>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.378 inches and 0.428 inches

Fastener Length:

Between 0.763 inches and 0.793 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.350 inches and 0.399 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.086 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.653 inches first hole and 0.703 inches first hole

Surface Finish:

32.0 microinches threads

Product Name:

Navy special project

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0