

View Online at <https://aerobasegroup.com/nsn/5305-00-573-7601>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.534 inches and 0.601 inches

**Fastener Length:**

Between 2.232 inches and 2.279 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.007 inches and 1.017 inches

**Grip Diameter:**

Between 0.4982 inches and 0.4991 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.678 inches and 1.698 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

300000 pounds per square inch

**Hardness Rating:**

55.0 rockwell c and 58.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel

**Material Specification:**

Vanadium alloy m-a, vanadium alloys steel co mfr ref single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0