NSN 5305-00-573-7601

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-573-7601 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.534 inches and 0.601 inches **Fastener Length:** Between 2.232 inches and 2.279 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.007 inches and 1.017 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel **Material Specification:** Vanadium alloy m-a, vanadium alloys steel co mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5305-00-573-7601

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0