

View Online at <https://aerobasegroup.com/nsn/5305-00-575-4620>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.888 inches and 2.000 inches

Fastener Length:

Between 1.938 inches and 2.000 inches

Head Style:

Fillister

Head Diameter:

Between 0.208 inches and 0.226 inches

Head Height:

Between 0.089 inches and 0.096 inches

Hole Diameter:

0.046 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Hole Quantity:

1

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

57000 pounds per square inch

Screw Material:

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 764 or copper alloy 770

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.