## NSN 5305-00-575-5340

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-575-5340 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.542 inches and 0.553 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.249 inches and 0.279 inches **Head Height:** Between 0.051 inches and 0.060 inches **Locking Feature:** Pellet or strip or patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel **Screw Material Specification:** Qq-s-637 federal specification single material response or astm a576 assn standard single material response or astm a108 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## **NSN 5305-00-575-5340** Machine Screw - Page 2 of 2



Fiig:

A500d0