NSN 5305-00-575-6292

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-575-6292 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.375 inches **Fastener Length:** Between 0.608 inches and 0.622 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.182 inches and 0.188 inches **Shoulder Diameter:** 0.247 inches first shoulder and 0.248 inches first shoulder **Shoulder Length:** 0.247 inches first shoulder and 0.253 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Locking element in threads Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-575-6292

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0