

View Online at <https://aerobasegroup.com/nsn/5305-00-576-1346>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.616 inches and 0.666 inches

Fastener Length:

Between 2.001 inches and 2.031 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.717 inches and 0.760 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Product Name:

Navy special project

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas586 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0