NSN 5305-00-576-2328

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-576-2328 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.232 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.327 inches and 0.338 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.020 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416 type 1 cl 3 federal specification 1st treatment response or qq-z-325 type 1 cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-576-2328

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0