NSN 5305-00-576-2343

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-576-2343 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.818 inches and 0.880 inches **Fastener Length:** Between 0.850 inches and 0.880 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf **Specification Data:** 80205-nas603 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-00-576-2343

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.