Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-576-7201



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 3.141 inches and 3.171 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Grip Length: Between 2.677 inches and 2.697 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4130 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unjf

Specification Data:

80205-nas584 professional/industrial association standard

NSN 5305-00-576-7201

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

