NSN 5305-00-577-2529



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-577-2529 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.351 inches and 0.382 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.694 inches and 0.742 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 14000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel or iron alloy 660 **Material Specification:** Nas 498 assn standard 1st material response or ams 5737 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-577-2529

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0